

The beam commissioning of China Accelerator for research on superheavy elements

Zhijun Wang, Yuan He, Weilong Chen, Xiaolong Chen,
Yuanshuai Qin, Chi Feng, Jianqiang Wu, weiping Dou,
Yue Tao, Huan Jia, Hanjie Cai, Yao Yang, Wang Lu

Institute of Modern Physics, CAS

Lanzhou, China

October 9 to 13, 2023, Geneva, Switzerland



Outline



- Motivation & background of CAFe² facility
- Challenges & solutions of beam commissioning
- Beam operation performance of CAFe² facility
- Perspective for the future

SuperHeavy Elements (SHE) (Z>103)


→ Evolution of the universe

Top science questions:



How many elements can exist on Periodic Table?

Are there stable high-atomic-number elements?

What are their chemistry properties for the heaviest elements?



More than ten artificially synthesised elements



Challenges:

- High beam intensity, sun as Calcium ions (5~10 pμA)
- Long beam time (a few months or years expt.)
- Rotating target withstanding high power beams
- High efficiency separator


Accelerators for SHE synthesis




Discover the new 113th element

RILAC


Country	Institute	Accelerator	Current/puA
Japan	RIKEN	RILAC	3
Russia	JINR	DC-280	3~6
Germany	GSI	UNILAC	1
American	LBNL	88-inch Cyclotron	1
China	IMP	CAFe²	3~10



UNILAC




Cyclotron DC-280




88-inch cyclotron

- 2011-2017, CAFe facility constructed, IMP cooperate with IHEP to demonstrate 10 mA CW beam of superconducting front-end Linac for ADS.
- 2018 to 2021, upgraded to test hundred kW beam;
- 2021, achieved 200kW@10mA proton beam.




ions	P, Alpha
Frequency	162.5 MHz
Current	10 mA
E _{out}	20MeV/u
Temp.	4.5 K



- Supported by “Strategic Priority Research Program” of the Chinese Academy of Sciences.

Heavy IS

China Accelerator Facility for Superheavy Elements (CAFe²)



Accelerator:

- ECR ion source
- Low energy beam transfer (LEBT)
- Radio frequency quadrupole (RFQ)
- Medium energy beam transfer (MEBT)
- High energy beam transfer (HEBT)

	Parameters	Parameters	Units
Ions	Ca ~ Zn	P/He	-
A/q	3	1/2	-
Energy	4.0-6.5	20/10	MeV/u
Current	1-10	1000	puA
Modes	Pluse/CW	Pluse/CW	-


Terminal:

- Differential pumping system
- Rotating target with actinide materia
- Gas-filled recoil separator (SHANS2)
- Detection svstem and DAO

Target:



- Highest beam current accelerator for superheavy elements synthesis
- Engaging in research on the synthesis of the 119th and 120th element.

IS+LEBT





b e a m



- Ions delivered from LECR5 (2021-2022):
 $^{16}\text{O}^{6+}$, $^{36}\text{Ar}^{12+}$, $^{40}\text{Ar}^{13+}$, $^{40}\text{Ca}^{13+}$, $^{55}\text{Mn}^{17+}$;
- Beam intensity: 2-10 pA;
- Extraction energy: 10 keV/u;



LECR5



RFQ




Parameter	Value
Operation Frequency	162.5 MHz
Charge-to-mass ratio	$1/3 \leq q/A \leq 1$
Beam current density	10 μ A
Cavity length	7047.5 mm
Input energy	10 keV/u
Output energy	1.33 MeV/u
Inter-vane Voltage	60 kV
E_{peak} (Kilpatrick factor)	21.49 MV/m (1.58)
Power loss	166 kW (@60 kV)
Q value	12745

Highlights in CAFe² RFQ cavity

- RF design for attenuation of the electrical field enhancement located in section gap and undercut
- Cooling channel design of **steady-state frequency shift**
- Auto-Conditioning and **Auto-Loading** of RF operation


RFQ UI





- ◆ H⁺: 18kW
- ◆ 40Ar¹³⁺: 165kW; 40Ca¹³⁺: 165kW
- ◆ 54Cr¹⁷⁺: 175kW
- ◆ 55Mn¹⁷⁺: 182kW

RFQ running power




MEBT




	Element	parameters
Magnet	Q120	23T/m
	Q150	27T/m
Buncher	IH-Buncher	162.5MHz/220kV
Beam diagnostics	ACCT	φ40
	BPM	162.5MHz/φ40
	FC	1uA~2mA
	Emittance slit+wire	0.016pi.mm.mrad (resolution)





HEBT



- ❑ **Doublet focusing**
- ❑ **Symmetric achromatic bending**
 - Dipole + Quad + Dipole
 - Cancel the energy spread contribute on transverse envelope
- ❑ **Triplet focusing to form small beam size**
 - 1E2 Pa to 1E-6 Pa in vacuum differential section
 - 6 thin tubes 1.5m long





❑ Low beam intensity

➤ beam current from 10 mA to 0.1 mA

❑ Small acceptance of terminal

➤ from A2D to A2T which including Vacuum differential section

❑ Undesigned hardware performance


➤ proton beam to 1/3 heavy ion beam

➤ cavity and solenoid operation parameters lower than design value

□ Low beam intensity

□ Challenges

- The BPM signal is weak and phase scanning is not as effective as it could be, It takes two or three hours.
- Frequent alteration of ions and energy



Phase scan curve of heavy ion beams

➡ □ Solution

- Replacing phase scanning with phase calculating methods

□ Low beam intensity

-phase and distance calibration

$$\Delta W = q \int_{z_0}^{z_0+L} E(z) \cos(\omega t(z) - \varphi_{\text{abs}} + \varphi_{\text{in}}) dz,$$

$$t(0) = 0, \omega t(z_0) = \varphi_{\text{abs}}$$

$$\varphi_{\text{in}} - \varphi_{\text{abs}} = \varphi_{\text{cav}} + \varphi_{\text{off}} - n \times 360^\circ$$

$\varphi_{\text{in}} - \varphi_{\text{abs}}$: beam phase related with energy and drift

φ_{off} : Offset with respect to the reference signal.

φ_{cav} : Cavity RF phase



- calibration experiment

$$\Delta\varphi = \frac{l f \times 360^\circ}{l_{\text{TOF}}} t_{\text{TOF}} + \varphi_{02} - \varphi_{01}$$

l_{TOF} : The distance between BPMs for measuring t_T

l : The distance between the two BPMs to be calibrate

φ_{01} & φ_{02} : Phase offsets of BPMs with respect to the reference signal.




BPM25&26 located at HEBT used to calibrate the distance and $\Delta\varphi$


BPM6-24 in cryomodule

Low beam intensity

- calibration experiment



Calibration of the resulting cavity and BPM position



Calibration results of ϕ_{off}

- less than 10 minutes to set up the cavities
- the deviation between measured energy and designed value is less than 1%

Calibration results for cavity distribution(mm)

1-1	1-2	1-3	1-4	1-5	1-6
0(origin)	577.39	1208.78	1851.12	2490.75	3135.43
2-1	2-2	2-3	2-4	2-5	2-6
4261.70	4902.74	5534.14	6168.49	6820.66	7466.04
3-1	3-2	3-3	3-4	3-5	3-6
8606.97	9245.62	9882.59	10522.20	11164.20	11829.20
4-1	4-2	4-3	4-4		
13063.80	13838.70	14625.20	15400.50		


Effectiveness of phase design methods in different particle scenarios

Particle	Designed(MeV)	Measured(MeV)	Deviation(%)
proton	9.289	9.285	0.04
$^{54}\text{Cr}^{17+}$	328.31	326.72	0.48
$^{48}\text{Ca}^{14+}$	262.64	261.57	0.41

□ Small acceptance of terminal


- Difficulty in beam commissioning

- Short time window for commissioning with calcium beam (^{48}Ca)
- Low acceptance of HEBT
 - ✓ The highest transmission efficiency $\sim 99\%$ in simulation
- Many parameters to be adjusted for right orbit and focusing
 - ✓ Doublet+Triplet+3 couples of steers
- Different energy requirement from the terminal
 - ✓ Energy scan, several times per week
 - ✓ Cavity off, solenoid adjust, energy/distribution both different
- Inaccurate current monitors
 - ✓ The last FC in $1\text{E}2\text{ Pa}$, readback much higher than real
- Time consuming in transmission efficiency optimization ~ 1 hours by manual means, **Trans $\sim 70\%$**



White: acceptance



Black: beam distribution in simulation



□ Small acceptance of terminal

-PSO / Brent Optimizer

- **Transmission efficiency optimization**
 - ✓ **Orbit:** Steers with BPMs, 1D scan
 - ✓ **Focusing:** Triplet with FCs+HRs
 - $D \uparrow F \downarrow D$, 1D scan, X/Y beam waist at same location
 - $D \uparrow F \uparrow D$, 1D scan, beam waist shift to the last HR
 - ✓ **Orbit:** Steers with FCs, 1D scan
- **Brent method**
 - ✓ Fast convergence speed
 - ✓ Adaptive step-size adjust
- **Local optimization, sensitive dependence on initial values**
- **20~30 minutes by online program, Trans~70%**




Brent method: ①②③→④, ①④③→⑤

Small acceptance of terminal

- Problems still need to be solved.
 - ✓ Higher transmission efficiency
 - ✓ Shorter tuning time
 - ✓ Multi-task coupling increases task difficulty

Recently, reinforcement learning (RL) is widely used in accelerator control.




- Challenges to apply RL in HEFT:
 - ✓ Highly nonlinearity complex system
 - ✓ Highly noise data from beam diagnostic devices

➤ Soft actor critic algorithm (SAC) is selected as our optimizer.

- ✓ Enhancing environment exploration
- ✓ Robust noise handling

Our plan: **Trained an RL controller in simulation environment and apply to real accelerator directly.**




Goal: Maximize the transmission efficiency of the HEBT.

Observation: 10 dimensions.

2 groups of BPMs, 5 HaloRings to beam loss measurement and the current of SS-FC1.

Adjustable variables: 12 degrees of freedom.


6 quadrupole magnets and 3 groups correctors.




Results in simulation (*with an insufficient trained model*):

- Without incident beam errors: 28 out of 50 groups achieve 90% or higher
- With incident beam errors: 25 out of 50 groups achieve 90% or higher

Without incident beam errors




With incident beam errors ± 0.5 mm.mrad



Preliminary results indicate the feasibility of our approach in this highly nonlinear optimization problem.



Undesigned hardware performance



Problems:



- 1/3 A/q particle beams with higher magnetic rigidity Vs. solenoids designed for proton beam
- with some superconducting cavities solenoid performance degradation

Undesigned hardware performance-longitudinal




- The beam energy requirement is the priority objective
- The synchronous phase slowly changes to 0deg to reduce RF defocusing
- Ensure longitudinal emittance out of SC. section within acceptance of HEBT

❑ Undesigned hardware performance-transverse



- Enlarge the overall beam envelop in the superconducting section to accomodate the insufficient focusing strength of solenoid
- Horizontal failure compensation is designed based on the principle of smoothing the overall envelope instead of local smoothing

Undesigned hardware performance



- The “peak-to-peak” matching principle is applied both for the local failure compensation section and quasi-periodic matching section to reduce the beam halo formation

CAFe² facility roadmap :



- **2021yrs: upgrading**
 - **03.16: ion source first beam extraction**
 - **05.01: linac commissioning**
 - **06.01: A&T commissioning**

- **2022.02-06:**
 - **Nuclide synthesis experiment (first time)**






- **2022yrs second half**
 - **Covid-19, Work at Home, intermittent Maintenance**

- **2023.02-07:**
 - **Officially continuous and stable operation**







超重加速器改造工作计划 (2021年) -- V20210316



Operation statistics





□ Operation statistics





Years	Num.	Particles	Target (17)	Total energy (MeV) (39)	CW current(puA)
2022	1	⁴⁰ Ar ¹³⁺	¹⁶⁹ Tm	178, 219	5.8
	2	⁴⁰ Ca ¹³⁺	¹⁶⁹ Tm	216, 217, 218, 219, 200, 223, 225, 227, 228	2.8
	3	⁵⁵ Mn ¹⁷⁺	¹⁶⁹ Tm, ¹⁵⁹ Tb, ²⁰⁹ Bi	238, 257, 270	2.7
2023	1	⁵⁴ Cr ¹⁷⁺	¹⁵⁹ Tb, ¹⁶⁵ Ho, ¹⁶⁹ Tm, ¹⁷⁵ Lu, ²⁰⁹ Bi, ¹⁸¹ Ta, ¹⁹⁷ Au	213, 215, 223, 225, 229, 235, 237, 241, 245, 247, 250, 253, 256, 258, 259, 263, 264, 265, 270, 274, 276, 290	1.8
	2	⁴⁰ Ar ¹²⁺	¹⁹⁷ Au, ²⁰⁹ Bi, ¹⁵⁹ Tb, ²³² Th	170, 175, 176, 182, 187, 193, 198, 204, 211, 206, 215, 221, 234,	8.3

- A new nuclide ²⁰⁴Ac has been published
- Other three new nuclides (²¹⁰Pa, ²¹⁸Np, ²³³Bk) to be published



Superconducting ECR ion source- SECRAL-II

Table.2. Typical performance of superconducting ECR ion source SECRAL-II [unit: euA].

Ion species	SECRAL-II	LECR5
$^{40}\text{Ar}^{13+}$	>200	80
$^{40}\text{Ca}^{13+}$	200*	75
$^{48}\text{Ca}^{15+}$	150*	40*
$^{58}\text{Fe}^{18+}$	100	30*
$^{64}\text{Ni}^{19+}$	100*	20*
$^{70}\text{Zn}^{21+}$	100*	20*



□ A new superconducting Ion source will be installed :

- Beam species: Ca-Zn
- Beam intensity: 5-15 puA

□ More effective commissioning schemes will be investigated:

- Machine learning assistance beam tuning

□ More detailed operation statistic



Superconducting ECR ion source- SECRAL-II

Table.2. Typical performance of superconducting ECR ion source SECRAL-II [unit: euA].

Ion species	SECRAL-II	LECR5
$^{40}\text{Ar}^{13+}$	>200	80
$^{40}\text{Ca}^{13+}$	200*	75
$^{48}\text{Ca}^{15+}$	150*	40*
$^{58}\text{Fe}^{18+}$	100	30*
$^{64}\text{Ni}^{19+}$	100*	20*
$^{70}\text{Zn}^{21+}$	100*	20*

□ A new superconducting Ion source will be installed :

- Beam species: Ca-Zn
- Beam intensity: 5-15 puA

□ More effective commissioning schemes will be investigated:

- Machine learning assistance beam tuning

□ More detailed operation statistic

Thanks for your attention